

## Detailed Specifications

|                                    |                              |
|------------------------------------|------------------------------|
| <b>Frame Width:</b>                | 80[mm]                       |
| <b>Frame Height:</b>               | 80[mm]                       |
| <b>Frame Depth:</b>                | 25[mm]                       |
| <b>Max. Air Flow:</b>              | 40.2[CFM]                    |
| <b>Max. Air Flow:</b>              | 1.13[m <sup>3</sup> per min] |
| <b>Max. Static Pressure:</b>       | 0.16[In H <sub>2</sub> O]    |
| <b>Max. Static Pressure:</b>       | 40.2[Pa]                     |
| <b>Fan Speed:</b>                  | 3400[RPM]                    |
| <b>Noise:</b>                      | 35[dB]                       |
| <b>Bearing Type:</b>               | Ball Bearing                 |
| <b>Nominal Voltage:</b>            | 24[V]                        |
| <b>Operating Voltage - Lower:</b>  | 10[V]                        |
| <b>Operating Voltage - Upper:</b>  | 26.4[V]                      |
| <b>Current:</b>                    | 0.14[A]                      |
| <b>Input Power:</b>                | 3.36[W]                      |
| <b>Mass:</b>                       | 94.8[g]                      |
| <b>Tach / Locked Rotor Output:</b> | Locked Rotor                 |
| <b>Status:</b>                     | EOL                          |