

## Detailed Specifications

<b>Frame Width:</b>	80[mm]
<b>Frame Height:</b>	80[mm]
<b>Frame Depth:</b>	38[mm]
<b>Max. Air Flow:</b>	105.94[CFM]
<b>Max. Air Flow:</b>	3[m <sup>3</sup> per min]
<b>Max. Static Pressure:</b>	1.43[In H <sub>2</sub> O]
<b>Max. Static Pressure:</b>	355[Pa]
<b>Fan Speed:</b>	7500[RPM]
<b>Noise:</b>	59.5[dB]
<b>Life Expectancy:</b>	N ~ P Class: 25 degree C 100,000 Hours Q ~ R Class: 25 degree C 80,000 Hours[L10]
<b>Bearing Type:</b>	Ball Bearing
<b>Nominal Voltage:</b>	24[V]
<b>Operating Voltage - Lower:</b>	14[V]
<b>Operating Voltage - Upper:</b>	26.4[V]
<b>Current:</b>	0.87[A]
<b>Input Power:</b>	20.9[W]
<b>Mass:</b>	240[g]
<b>IP Rating:</b>	IP68/IP69K
<b>Tach / Locked Rotor Output:</b>	No
<b>Status:</b>	Active

Harsh/Wet Environment Fans